

# (12) UK Patent Application (19) GB (11) 2 351 308 (13) A

(43) Date of Printing by UK Office 27.12.2000

(21) Application No 0019447.2

(22) Date of Filing 17.12.1999

(30) Priority Data

(31) 60112833 (32) 18.12.1998 (33) US

(86) International Application Data  
PCT/US99/30290 En 17.12.1999

(87) International Publication Data  
WO00/36266 En 22.06.2000

(51) INT CL<sup>7</sup>

E21B 23/04 4/18

(52) UK CL (Edition R )

E1F FEE FHJ FKU

(56) Documents Cited by ISA

WO 97/08418 A

(58) Field of Search by ISA

INT CL<sup>7</sup> E21B

(71) Applicant(s)

Western Well Tool Inc  
(Incorporated in USA - California)  
2946 E Coronado Street, Anaheim, California 92806,  
United States of America

(74) Agent and/or Address for Service

Sommerville & Rushton  
45 Grosvenor Road, ST ALBANS, Herts., AL1 3AW,  
United Kingdom


(72) Inventor(s)

Ronald E Beaufort  
Duane Bloom  
Norman Bruce Moore

(54) Abstract Title

**Electro-hydraulically controlled tractor**

(57) A tractor (20) for moving within a borehole comprises body and two propulsion assemblies (24, 26) that are longitudinally movably engaged with the body. The tractor body has annular pistons (34, 36, 38, 40) configured to receive hydraulic thrust to propel the body longitudinally. Each propulsion assembly includes a gripper (42, 52) and propulsion cylinders (44, 46, 48, 50). The gripper has an actuated position in which the gripper limits relative movement between the gripper and the inner surface of the borehole, and a retracted position in which the gripper permits free relative movement between the gripper and the inner surface of a borehole. Each propulsion cylinder contains one of the pistons. The tractor includes a control assembly (30) having valves and hydraulic circuitry which control the sequencing of fluid distribution to the propulsion cylinders, and of the actuation and retraction of the grippers. A throttle valve (54) controls the fluid flowrate to the pistons.



GB 2 351 308 A